

Application/Control Number 09/779,288 filed 2/8/01

## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the Application:

### Listing of the Claims

#### 5 Pending Claims

1.- 7. (canceled)

8. (previously presented) The composition according to claim 24 further comprising an effective amount of one or more Diesel fuel additives selected from the group consisting of  
10 copolymers of ethylene and vinyl acetate, which enhances cold flow properties of Diesel fuel.


9 - 10 (canceled)

11. (currently amended) The composition according to claim 26 [[10]] wherein at least 5 percent of the oxygen is  
15 contained in cyclic benzylic diketones.

12. (previously presented) The composition according to claim 11 further comprising an effective amount of one or more fuel additives which enhance desired fuel properties.

13. (original) A composition for fuel or blending  
20 component for fuels, which are liquid at ambient conditions, which composition comprises: as a predominant component petroleum distillates which contain less than 15 ppm sulfur, and oxygen-containing organic compounds derived from natural petroleum in amounts such that the oxygen content of the fuel is in a range from  
25 about 0.2 percent to about 10 percent oxygen, with the proviso that at least 10 percent of the oxygen is contained in aryl oxygenates represented by

Application/Control Number 09/779,288 filed 2/8/01



5

where  $R_1$  are independently selected from the group consisting of hydrogen and hydrocarbon radicals containing from 1 to about 10 carbon atoms,  $x$  is an integer from 1 to 4;  $R_2$  are independently  
 10 selected from the group consisting of hydrogen, hydroxyl, carbonyl oxygen and organic moieties containing from 1 to about 10 carbon atoms, and  $y$  is an integer from 1 to 3.

14. (canceled)

15. to 22. (withdrawn)

15 23. (canceled)

24. (currently amended) A fuel for use in compression ignition internal combustion engines, comprising: as a predominant component organic distillates derived from natural petroleum, and one or more oxygen-containing organic compounds in amounts  
 20 such that the oxygen content of the fuel is in a range from about 0.2 percent to about 10 percent oxygen with the proviso that

$$[10^\circ \text{C.} + (\text{IBP}) \text{ composition}] > (\text{IBP}) \text{ distillates},$$



where (IBP) composition is the initial boiling point of the composition and (IBP) distillates, is the initial boiling point of the  
 25 distillates, and wherein the predominant component comprises alkanes containing from 5 to about 15 carbon atoms of which at least about 85 percent are normal alkanes, and the fuel exhibits a

Application/Control Number 09/779,288 filed 2/8/01

suitable flash point of at least 38° C. as measure by ASTM D93, and contains less than 15 ppm sulfur.

25. (currently amended) A fuel for use in compression  
 5 [[spark]] ignition internal combustion engines, comprising: as a  
 predominant component organic distillates derived from natural  
petroleum, and one or more oxygen-containing organic compound  
 selected from the group consisting of aryl oxygenates of type II  
 and type III represented by

10



- 15 in amounts such that the oxygen content of the fuel is in a range  
 from about 0.2 percent to about 10 percent oxygen, and wherein  
 the fuel exhibits a suitable flash point of at least 49°C. ~~Reid vapor~~  
~~pressure of at least 6 psi~~ and contains less than 15 ppm sulfur.

26. (currently amended) A composition for fuel or blending  
 20 component for fuels which are liquid at ambient conditions, which  
 composition comprises: as a predominant component organic  
 distillates which contain less than 15 ppm sulfur, and oxygen-  
 containing organic compounds derived from natural petroleum in  
 amounts such that the oxygen content of the fuel is in a range from  
 25 about 0.2 percent to about 10 percent oxygen with the proviso that


$$[10^{\circ} \text{C.} + (\text{IBP}) \text{ composition}] > (\text{IBP}) \text{ distillates,}$$

Application/Control Number 09/779,288 filed 2/8/01

where (IBP) composition is the initial boiling point of the composition and (IBP) distillates, is the initial boiling point of the distillates, wherein the predominant component is a mixture of organic compounds derived from natural petroleum, and wherein  
5 at least 10 percent of the oxygen is contained in cyclic benzylic ketones.

27. (currently amended) The composition according to claim 13 wherein at least 10 percent of the oxygen is further contained in Type II aryl oxygenates represented by

10



where R is hydrogen or a hydrocarbon radical containing from 1 to  
15 about 10 carbon atoms.